

PRODUCT NAME : MFCARBGC B612
 APPLICATION AREA : GOLD RECOVERY
 SOURCE : COCONUT SHELL
 ACTIVATION AGENT : STEAM/AIR
 MESH SIZE : 6X12 USS MESH

Parameter	Unit	Specification	Test Method
Moisture	%	5 max.	ASTM D2867
CTC Adsorption	%	50 min	ASTM D3467
Apparent density	Kg/m ³	480 -550	ASTM D2854
Ash Content	%	4 max.	ASTM D2866
Iodine	mg/gm	1000	ASTM D4607
pH	-	9-11	ASTM D3838
Ball Pan Hardness	%	99 min	ASTM D3802
Platelets	%	4% max	AARL
Attrition	%	2.0% max	AARL
K value		26 kg/ton	AARL
R- value	%	50 %	AARL

Particle Size Distribution			
Mean Particle Diameter – 2.48 mm			
+6 USS MESH	%	5 max.	ASTM D2862
-12 USS MESH	%	5 max.	ASTM D2862

PACKING: The material is packaged in 500kgs net in polywoven bags or 25kgs net in PP bags with inner lining will be shrink wrapped and palletized in to fumigated Pallets as per ISPM 15 standard.

STORAGE: Store the material in a cool dry area, away from sunlight. **SHELF LIFE:** More than 5 Years when keeping in proper packed condition

LABELING: The label displays the product name, lot number, net weight, gross weight, manufacturer name & address and other information or marks as required by the customer.

